AT-AR441S

Secure ADSL Router

AT-AR441S

1 x ADSL port
5 x 10/100Base-T ports
1 x PIC
1 x Asynchronous port

ADSL Business Class Routing Solution

The AT-AR441S is a competitively priced, business-class, secure ADSL router. This desktop, broadband router allows businesses to take advantage of cost effective DSL connections without compromising on bandwidth, throughput, features, or security.

The AT-AR441S has been designed with the needs of the branch office or small to medium business in mind and comes with dying gasp and the WAN back-up features businesses expect.

The AT-AR441S comes with, or has as optional extras, all the software features necessary for a product of this type, such as:

- An extensive VPN capability
- Comprehensive ADSL support
- An extensive QoS suite
- Multiple routing protocols
- A comprehensive configuration and management suite

Extensive VPN Capability

The AT-AR441S provides extensive IPsec based VPN capability, allowing the interconnection of branch offices, remote tele-workers, and other users who require secure access to a corporate network. This capability provides a cost effective alternative to long-distance dial-in, leased line or frame-relay connections. The AT-AR441S comes complete with integrated hardware acceleration to maximise encryption and throughput during secure communication. The product is compatible with industry standard IPsec VPN clients.

Security

In addition to hardware-based encryption, the AT-AR441S comes with other security features, such as traffic filtering with event logging. Traffic filtering uses the source and destination address, port, protocol and TCP packet type to provide control over traffic that passes through the AT-AR441S. The AT-AR441S' Stateful Inspection firewall provides an increased level of security, and HTTP and SMTP proxies provide improved control over web and mail communication.

Software Quality of Service

The AlliedWare™ operating system provides advanced Quality of Service (QoS) and traffic shaping features. There are five key QoS features available on the AT-AR441S:

- Bandwidth Metering
- RED Curves
- Mixed Scheduling
- Virtual Bandwidth
- Dynamic Application Recognition (DAR)

Software QoS also supports eight queues per interface. DAR is used to snoop for session setup exchanges and dynamically create classifiers that match the voice and video packets in the session. For more information, see the Allied Telesis Advanced QoS White Paper available on our website.

Flexibility of Modular Routing

A Port Interface Card (PIC) port on the AT-AR441S provides businesses with a high degree of flexibility, enabling them to future proof their investment, obtain additional functionality or make use of WAN back-up options. For example, a backup WAN card, such as an ISDN card, can be installed in the PIC port enabling businesses to protect themselves against ADSL downtime. The PIC options available also enable businesses to achieve a higher LAN density without purchasing an additional switch. The AT-AR441S PIC port is compatible with a range

Key Features

- 1 x Annex B ADSL port
- Modular Router – 1 PIC that supports a range of WAN interfaces
- Integrated encryption engine supporting DES, 3DES and AES
- 5 x 10/100 Mbps Ethernet switched LAN ports, any port can also be reconfigured as a DMZ
- Secure VPN capability with IPsec
- Automatic WAN back-up
- Stateful inspection firewall
- QoS
- SNMP and CLI management
- Web GUI
- Dying gasp
- Conforms to U-R2
- RoHS compliant
- Optional features available such as:
  - IPv6
  - BGP-4
  - Server Load Balancing

of PICs, including BRI/PRI ISDN, high speed E1/T1, Synchronous, and FXS VoIP.

Performance

The AT-AR441S modular router provides a significant improvement in the performance of Allied Telesis' modular router family. The 300MHz CPU within the AT-AR441S ensures that large packets are forwarded at wire-speed and that small packets are forwarded with minimal delay.

Comprehensive Management and Configuration

The AT-AR441S comes with a comprehensive suite of management features and is also compatible with SNMP based management packages. An extensive command set is available via the Command Line Interface (CLI), and a browser-based Graphical User Interface (GUI) is also provided to simplify configuration and management of the AT-AR441S. The GUI provides access to default set-ups in key management areas and provides access to regional settings. Allied Telesis' SNMP support extends to SNMPv3, which provides the option of secure management.

Feature Summary

ADSL

Annex B
G992.1 G.DMT
ANSI T1.413
Downstream data rate: Up to 8 Mbps [1]
Upstream data rate: Up to 640Kbps [1]
Connector: RJ11
30 PVCs
Dying gasp
RFC 2684 MPoA Encapsulation over ATM (IP, bridging & encapsulated routing)
RFC 2364 PPPoA
RFC 2516 PPPoE
RFC 2225 IPoA Classical IP & ARP over ATM

Routing

PPP and IP Routing
RIP V1 & V2
DHCP
OSPF
DVMRP [2] (including draft_ietf_idmr_dvmrp_v3_10)
BGP-4 [2]
IPX
NAT

WAN Protocols

X.25
Frame Relay

VPN

L2TP
NAT-T
Windows® XP VPN client interoperability

Security

Hardware acceleration
IPSec
IKE
ISAKMP
PKI
SSH
SSL
SMTP & HTTP Proxy
Authentication: RADIUS, TACACS, MD5, PAP, CHAP
Encryption: DES, 3DES, AES
IP Filtering
Firewall: Stateful Inspection

QOS

IP
- RSVP
- IP Packet Prioritisation
- Prioritisation based on TOS & Diffserve
- Low latency queuing (LLQ)
- Weighted fair queuing

ATM
- Per VC queuing and traffic shaping
- Unspecified bit rate (UBR)
- Constant bit rate (CBR)
- Nonreal-time variable bit rate (VBRnrt)

Management

CLI
Browser Based GUI
SNMPV3

IPv6

RIPng
IPv6 RFC 2460
Neighbour discovery RFC 2461
Stateless address autoconfiguration RFC 2462
ICMP v6 RFC 2463
Transmission of IPv6 packets RFC 2464
Connection of IPv6 domains via IPv4 clouds RFC 3056.
PIM

[1] *Maximum specified by ADSL chip-set vendor, achieved speeds are dependent on DSLAM and line characteristics, including length*

[2] *Software features requiring the purchase of a feature licence*

Reliability

MTBF: 120 000 hrs

Redundancy

External modem backup
VRRP

Hardware Features

1 x ADSL Port
5 x 10/100 Mbps Switch
1 x Async Console port
1 x Port Interface Card (PIC)
DMZ port: Obtained by configuring one of the switch ports

Processor

300MHz
Internal security encryption engine

Memory

64MB Ram
16MB Flash

Power Characteristics

Input Voltage: 100-240 VAC, 50-60 Hz
Max Power Consumption: 40W
Internal Battery Backup (1 year)

Physical Dimensions

Dimensions: 335mm (W) x 44mm (H) x 180mm (D)
Weight: 1.96kg

Environmental

Operating Temp: 0°C to 50°C
Storage Temp: -25°C to 70°C
Operating relative humidity: 5 to 80% non-condensing
Acoustic Level: ANSI S12.10 – Desktop 47 dBA

Approvals & Certifications

U-R2
UL
TUV
UL60950
EN60950
EN55022 class A
EN55024
FCC class A
VCCI class A
AS/NZS CISPR22 class A

Optional Extras

Rack mount accessory kit: 990-000023-00
Wall mount accessory kit: 990-000025-00

Port Interface Cards:

- AT-AR020 Single configurable E1/T1 interface that supports channelized/ unchannelized Primary Rate ISDN/Frame Relay
- AT-AR021S (V2) Single Basic Rate ISDN (S/T) interface
- AT-AR023 Single Synchronous port up to 2Mbps to an external CSU/DSU (AT-V.35-DTE-00 or AT-V.21-DTE-00 cable required)
- AT-AR024 Four Asynchronous RS232 interfaces to 115Kbps
- AT-AR027 Two VoIP FXS ports

Country of Origin

China

Standards and Protocols

Software Release 2.9.1

BGP-4

RFC 1771 Border Gateway Protocol 4
RFC 1966 BGP Route Reflection
RFC 1997 BGP Communities Attribute
RFC 1998 Multi-home Routing
RFC 2385 Protection of BGP Sessions via the TCP MD5 Signature Option
RFC 2439 BGP Route Flap Damping
RFC 2858 Multiprotocol Extensions for BGP-4
RFC 2918 Route Refresh Capability for BGP-4
RFC 3065 Autonomous System Confederations for BGP
RFC 3392 Capabilities Advertisement with BGP-4

Encryption

RFC 1321 MD5
RFC 2104 HMAC
RFC 2451 The ESP CBC-Mode Cipher Algorithms
FIPS 180 SHA-1
FIPS 186 RSA
FIPS 197 AES
FIPS 46-3 DES
FIPS 46-3 3DES

Ethernet

RFC 894 Ethernet II Encapsulation
IEEE 802.1D MAC Bridges
IEEE 802.1G Remote MAC Bridging
IEEE 802.1Q Virtual LANs
IEEE 802.2 Logical Link Control
IEEE 802.3ac VLAN TAG
IEEE 802.3u 100BASE-T
IEEE 802.3x Full Duplex Operation

General Routing

RFC 768 UDP
RFC 791 IP
RFC 792 ICMP
RFC 793 TCP
RFC 826 ARP
RFC 903 Reverse ARP
RFC 925 Multi-LAN ARP
RFC 950 Subnetting, ICMP
RFC 1035 DNS
RFC 1027 Proxy ARP
RFC 1055 SLIP
RFC 1122 Internet Host Requirements
RFC 1144 Van Jacobson's Compression
RFC 1256 ICMP Router Discovery Messages
RFC 1288 Finger
RFC 1332 The PPP Internet Protocol Control Protocol (IPCP)
RFC 1334 PPP Authentication Protocols
RFC 1377 The PPP OSI Network Layer Control Protocol (OSINLCP)
RFC 1378 The PPP AppleTalk Control Protocol (ATCP)
RFC 1518 CIDR
RFC 1519 CIDR
RFC 1542 BootP
RFC 1552 The PPP Internetworking Packet Exchange Control Protocol (IPXCP)
RFC 1570 PPP LCP Extensions
RFC 1582 RIP on Demand Circuits
RFC 1598 PPP in X.25
RFC 1618 PPP over ISDN
RFC 1661 The Point-to-Point Protocol (PPP)
RFC 1701 GRE
RFC 1702 GRE over IPv4
RFC 1762 The PPP DECnet Phase IV Control Protocol (DNCP)
RFC 1812 Router Requirements
RFC 1877 PPP Internet Protocol Control Protocol Extensions for Name Server Addresses
RFC 1918 IP Addressing
RFC 1962 The PPP Compression Control Protocol (CCP)
RFC 1968 The PPP Encryption Control Protocol (ECP)
RFC 1974 PPP Stac LZS Compression Protocol
RFC 1978 PPP Predictor Compression Protocol
RFC 1989 PPP Link Quality Monitoring
RFC 1990 The PPP Multilink Protocol (MP)
RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)
RFC 2125 The PPP Bandwidth Allocation Protocol (BAP) / The PPP Bandwidth Allocation Control Protocol (BACP)
RFC 2131 DHCP
RFC 2390 Inverse Address Resolution Protocol
RFC 2516 A Method for Transmitting PPP Over Ethernet (PPPoE)
RFC 2661 L2TP
RFC 2822 Internet Message Format
RFC 2878 PPP Bridging Control Protocol (BCP)
RFC 3046 DHCP Relay Agent Information Option
RFC 3232 Assigned Numbers
RFC 3993 Subscriber-ID Sub-option for DHCP Relay Agent Option
ISO 10589, ISO 10589 Technical Corrigendums 1, 2, 3, ISO Intermediate System-to-Intermediate System "ISO 8473, relevant parts of ISO 8348(X.213), ISO 8343/
Add2, ISO 8648, ISO 8648, ISO TR 9577 Open System Interconnection"
ISO 9542 End System to Intermediate System Protocol
"IPX Router Specification", v1.2, Novell, Inc., Part Number 107-000029-001
Encapsulation of IPsec Packets
http://www.iana.org/assignments/bootp-dhcp-parameters BootP and DHCP parameters

General Routing and Firewall

RFC 3022 Traditional NAT
draft-ietf-ipsec-nat-t-ike-08.txt Negotiation of NAT-Traversal in the IKE
draft-ietf-ipsec-udp-encaps-08.txt UDP Encapsulation of IPsec Packets

IP Multicasting

RFC 1075 DVMRP
RFC 1112 Host Extensions
RFC 2236 IGMPv2
RFC 2362 PIM-SM
RFC 2715 Interoperability Rules for Multicast Routing Protocols
RFC 3973 PIM-DM
draft-ietf-idmr-dvmrp-v3-9 DVMRP

IPsec

RFC 1829 Ipsec algorithm
RFC 1828 IP Authentication using Keyed MD5
RFC 2395 Ipsec Compression - LZS
RFC 2401 Security Architecture for IP
RFC 2402 AH - IP Authentication Header
RFC 2403 IPsec Authentication - MD5
RFC 2404 IPsec Authentication - SHA-1
RFC 2405 IPsec Encryption - DES
RFC 2406 ESP - IPsec encryption
RFC 2407 IPsec DOI
RFC 2408 ISAKMP
RFC 2409 IKE
RFC 2410 IPsec encryption - NULL
RFC 2411 IP Security Document Roadmap
RFC 2412 OAKLEY
RFC 3173 IPComp - IPsec compression

IPv6

RFC 1981 Path MTU Discovery for IPv6
RFC 2080 RIPng for IPv6
RFC 2365 Administratively Scoped IP Multicast
RFC 2375 IPv6 Multicast Address Assignments
RFC 2460 IPv6
RFC 2461 Neighbour Discovery for IPv6
RFC 2462 IPv6 Stateless Address Autoconfiguration
RFC 2463 ICMPv6
RFC 2464 Transmission of IPv6 Packets over Ethernet Networks
RFC 2465 Allocation Guidelines for Ipv6 Multicast Addresses Management Information Base for IP Version 6: Textual Conventions and General Group
RFC 2466 Management Information Base for IP Version 6: ICMPv6 Group
RFC 2472 IPv6 over PPP
RFC 2526 Reserved IPv6 Subnet Anycast Addresses
RFC 2529 Transmission of IPv6 over IPv4 Domains without Explicit Tunnels
RFC 2710 Multicast Listener Discovery (MLD) for IPv6
RFC 2711 IPv6 Router Alert Option
RFC 2851 Textual Conventions for Internet Network Addresses
RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers
RFC 3056 Connection of IPv6 Domains via IPv4 Clouds
RFC 3307 Allocation Guidelines for IPv6 Multicast Addresses
RFC 3315 DHCPv6
RFC 3484 Default Address Selection for IPv6
RFC 3513 IPv6 Addressing Architecture
RFC 3587 IPv6 Global Unicast Address Format
RFC 3596 DNS Extensions to support IPv6
RFC 3810 Multicast Listener Discovery Version 2 (MLDv2) for IPv6

Management

RFC 1155 MIB
RFC 1157 SNMP
RFC 1212 Concise MIB definitions
RFC 1213 MIB-II
RFC 1493 Bridge MIB
RFC 1643 Ethernet MIB
RFC 1657 Definitions of Managed Objects for BGP-4 using SMIv2
RFC 2011 SNMPv2 MIB for IP using SMIv2
RFC 2012 SNMPv2 MIB for TCP using SMIv2
RFC 2096 IP Forwarding Table MIB
RFC 2576 Coexistence between V1, V2, and V3 of the Internet-standard Network Management Framework
RFC 2578 Structure of Management Information Version 2 (SMIv2)
RFC 2579 Textual Conventions for SMIv2
RFC 2580 Conformance Statements for SMIv2
RFC 2665 Definitions of Managed Objects for the Ethernet-like Interface Types
RFC 2674 Definitions of Managed Objects for Bridges with Traffic Classes, Multicast Filtering and Virtual LAN

Extensions (VLAN)
RFC 2790 Host MIB
RFC 2819 RMON (groups 1,2,3 and 9)
RFC 2856 Textual Conventions for Additional High Capacity Data Types
RFC 2863 The Interfaces Group MIB
RFC 3164 Syslog Protocol
RFC 3289 Management Information Base for the Differentiated Services Architecture
CDP
RFC 3410 Introduction and Applicability Statements for Internet-Standard Management Framework
RFC 3411 An Architecture for Describing SNMP Management Frameworks
RFC 3412 Message Processing and Dispatching for the SNMP
RFC 3413 SNMP Applications
RFC 3414 User-based Security Model (USM) for SNMPv3
RFC 3415 View-based Access Control Model (VACM) for the SNMP
RFC 3416 Version 2 of the Protocol Operations for SNMP
RFC 3417 Transport Mappings for the SNMP
RFC 3418 MIB for SNMP
RFC 3636 Definitions of Managed Objects for IEEE 802.3 MAUs
RFC 3768 VRRP
draft-ietf-bridge-8021x-00.txt Port Access Control MIB
IEEE 802.1AB LLDP

OSPF

RFC 1245 OSPF protocol analysis
RFC 1246 Experience with the OSPF protocol
RFC 1586 OSPF over Frame Relay
RFC 1793 Extending OSPF to Support Demand Circuits
RFC 2328 OSPFv2
RFC 3101 The OSPF Not-So-Stubby Area (NSSA) Option

QoS

RFC 2205 Reservation Protocol
RFC 2211 Controlled-Load
RFC 2474 DCSP in the IPv4 and IPv6 Headers
RFC 2475 An Architecture for Differentiated Services
RFC 2597 Assured Forwarding PHB Group
RFC 2697 A Single Rate Three Color Marker
RFC 2698 A Two Rate Three Color Marker
RFC 3246 An Expedited Forwarding PHB (Per-Hop Behavior)
IEEE 802.1p Priority Tagging

RIP

RFC 1058 RIPv1
RFC 2082 RIP-2 MD5 Authentication
RFC 2453 RIPv2

Security

RFC 959 FTP
RFC 1413 IDP
RFC 1492 TACACS
RFC 1779 X.500 String Representation of Distinguished Names.
RFC 1858 Fragmentation
RFC 2284 EAP
RFC 2510 PKI X.509 Certificate Management Protocols
RFC 2511 X.509 Certificate Request Message Format
RFC 2559 PKI X.509 LDAPv2
RFC 2585 PKI X.509 Operational Protocols
RFC 2587 PKI X.509 LDAPv2 Schema
RFC 2865 RADIUS
RFC 2866 RADIUS Accounting
RFC 3280 X.509 Certificate and CRL profile
draft-grant-tacacs-02.txt TACACS+
Draft-IETF-PKIX-CMP-Transport-Protocols-01 Transport Protocols for CMP
draft-ylonen-ssh-protocol-00.txt SSH Remote Login Protocol
IEEE 802.1x Port Based Network Access Control
PKCS #10 Certificate Request Syntax Standard
Diffie-Hellman

Services

RFC 854 Telnet Protocol Specification
RFC 855 Telnet Option Specifications
RFC 856 Telnet Binary Transmission
RFC 857 Telnet Echo Option
RFC 858 Telnet Suppress Go Ahead Option
RFC 932 Subnetwork addressing scheme
RFC 951 BootP
RFC 1091 Telnet terminal-type option
RFC 1305 NTPv3
RFC 1350 TFTP
RFC 1510 Network Authentication
RFC 1542 Clarifications and Extensions for the Bootstrap Protocol
RFC 1945 HTTP/1.0
RFC 1985 SMTP Service Extension
RFC 2049 MIME
RFC 2068 HTTP/1.1
RFC 2156 MIXER
RFC 2217 Telnet Com Port Control Option
RFC 2821 SMTP

SSL

RFC 2246 The TLS Protocol Version 1.0
draft-freier-ssl-version3-02.txt SSLv3

X.25

RFC 1356 Multiprotocol Interconnect on X.25 and ISDN in the Packet Mode
ITU-T Recommendations X.25 (1988), X.121 (1988). X.25

xDSL

RFC 2225 IPoA Classical IP & ARP over ATM
RFC 2364 PPP Over AAL5
RFC 2684 IpoE Multiprotocol encapsulation over ATM
ANSI T1.413 ADSL Metallic Interface
ITU-T G.992.1 (G.DMT) ADSL Transceivers
ITU-T G.992.1 (G.DMT) Annex B ADSL Transceivers

ISDN

ANSI T1.231-1997 Digital Hierarchy - Layer 1 In-Service Digital Transmission Performance Monitoring Standardization
ANSI T1.403-1995 Telecommunications - Network-to-Customer Installation - DS1 Metallic Interface
ANSI T1.408-1990 ISDN Primary Rate - Customer Installation Metallic Interfaces, Layer 1 Specification
AT&T TR 54016-1989 Requirements for Interfacing Digital Terminal Equipment to Services Employing the Extended Superframe Format
Austel TS 013.1:1990 General Requirements for Customer Equipment Connected to ISDN Basic Rate Access - Vol. 1: Customer Equipment Access Interface Specifications
Bellcore SR-3887 1997 National ISDN Primary Rate Interface
ETS 300 012:1992 Integrated Services Digital Network (ISDN); Basic user-network interface; Layer 1 specification and test principles
ETS 300 102-1:1990 Integrated Services Digital Network (ISDN);User-network interface layer 3;Specifications for basic call control
ETS 300 102-2:1990 Integrated Services Digital Network (ISDN); User-network interface layer 3; Specifications for basic call control; Specification Description Language (SDL) diagrams
ETS 300 125:1991 Integrated Services Digital Network (ISDN); User-network interface data link layer specification; Application of CCITT Recommendations Q.920/I.440 and Q.921/I.441
ETS 300 153:1992 Integrated Services Digital Network (ISDN);Attachment requirements for terminal equipment to connect to an ISDN using ISDN basic access (Candidate NET 3 Part 1)
ETS 300 156:1992 Integrated Services Digital Network (ISDN); Attachment requirements for terminal equipment to connect to an ISDN using ISDN primary rate access (Candidate NET 5)
ETS 300 011:1992 Integrated Services Digital Network (ISDN); Primary rate user-network interface; Layer 1 specification and test principles
G.706 (1988) Frame Alignment and CRC Procedures Relating to Basic Frame Structures Defined in G.704
G.794 (1988) Characteristics of 24-channel transmultiplexing equipments
German Monopol (BAPT 221) Type Approval Specification for Radio Equipment for Tagging and Identification
I.120 (1988) Integrated services digital networks (ISDNs)
I.121 (1988) Broadband aspects of ISDN
I.411 (1988) ISDN user-network interface reference configurations
I.430 (1988) Basic user-network interface - Layer 1 specification
I.431 (1988) Primary rate user-network interface - Physical layer specification
ITU-T G.703 Physical/electrical characteristics of hierarchical digital interfaces
ITU-T G.704 Synchronous frame structures used at 1544, 6312, 2048, 8488 and 44736 kbit/s hierarchical levels
ITU-T G.706 Frame Alignment and CRC Procedures Relating to Basic Frame Structures Defined in G.704
ITU-T Q.922 ISDN data link layer specification for frame mode bearer services
ITU-T G.703 (1972) Physical/electrical characteristics of hierarchical digital interfaces
Japan NTT I.430-a Leased Line Basic Rate User-Network Interface Layer 1-Specification
New Zealand Telecom TNA 134 Telecom ISDN User-Network Interface: Layer 3: PART B Basic Call Control Procedures
Q.920 (1988) Digital subscriber Signalling System No.1 (DSS1) - ISDN user-network interface data link layer - General aspects
Q.921 (1988) ISDN user-network interface - Data link layer specification
Q.930 (1988) Digital subscriber Signalling System No. 1 (DSS 1) - ISDN user-network interface layer 3 - General aspects
Q.931 (1988) Digital subscriber Signalling System No. 1 (DSS 1) - ISDN user-network interface layer 3 specification for basic call control
Rockwell Bt8370 Fully Intergrated T1/E1 Framer and Line Interface data sheet
Technical Reference of Frame Relay Interface, Ver. 1, November 1993, Nippon Telegraph and Telephone Corporation. Ver. 1, November 1993, Nippon Telegraph

and Telephone Corporation.
ACA TS 013.2:1990 General Requirements for Customer Equipment Connected to ISDN Basic Rate Access, Vol 2: Conformance Testing Specifications
ACA TS 014.1:1990 General Requirements for Customer Equipment Connected to ISDN Primary Rate Access, Vol 1: Customer Access Interface Specifications
ACA TS 014.2:1990 General Requirements for Customer Equipment Connected to ISDN Primary Rate Access, Vol 2: Conformance Testing Specifications

Frame Relay

RFC 1490, 2427 Multiprotocol Interconnect over Frame Relay
ANSI T1S1 Frame relay

VoIP

RFC 2543 SIP
G.711 A/µ law Pulse code modulation (PCM) of voice frequencies
G.723.1 Dual rate speech coder for multimedia communications transmitting at 5.3 and 6.3 kbit/s
G.729 A/B (Optional) Coding of speech at 8 kbit/s using conjugate-structure algebraic-code-excited linear-prediction (CS-ACELP)
H.323 v2 Packet-based multimedia communications systems

Ordering Information

AT-AR441S Secure ADSL Router
Order Number: 990-001129-xx

Where xx =
10 for U.S. power cord
20 for no power cord
30 for U.K. power cord
40 for Australian power cord
50 for European power cord

AT-AR441S ships with both a rack mount kit and a wall mount kit.

Order number for an additional rack mount kit:
990-000024-00

Order number: for an additional wall mount kit:
990-000025-00

Port Interface Card Options

AT-AR020
Single configurable E1/T1 interface that supports channelized/unchannelized Primary Rate ISDN/Frame Relay
Order Number: 990-001304-00

AT-AR021S (V2)
Single Basic Rate ISDN (S/T) interface
Order Number: 990-001103-00

AT-AR023
Single Synchronous port up to 2Mbps to an external CSU/DSU (AT-V.35-DTE-00 or AT-V.21-DTE-00 cable required)
Order number: 990-001104-00

AT-AR024
Four Asynchronous RS232 interfaces to 115Kbps
Order number: 990-001105-00

AT-AR027
Two VoIP FXS ports
Order number: 990-001356-00

Software upgrade options

AT-AR400 – ADVL3UPGRD
AR400 series advanced layer 3 upgrade
- IPv6
- BGP-4
- Server Load Balancing

Order number: 980-10021-00

About Allied Telesis

Allied Telesis founded in 1987 and now has offices around the globe, over 3,000 employees and over $500M of worldwide annual revenue. The attributes which have led Allied Telesis to achieve its leading position in the enterprise, operator and connectivity business segments can be summarized by four key elements: its business focus on networking technology for professional markets, where ATI has proved to be the only company capable of providing a total end-to-end solution at a high price/performance ratio; the ability to handle every aspect of its own products from design to marketing; the development of components and solutions which accommodate flexible, efficient and reliable network construction; and support from sound warranty terms and quality services. Allied Telesis connects the IP world efficiently thanks to affordable and highly reliable network solutions. For more information see: www.alliedtelesis.com

Service & Support

Allied Telesis provides value-added support services for its customers under its Net.Cover℠ programs. For more information on Net.Cover℠ support programs available in your area, contact your Allied Telesis sales representative or visit our website. www.alliedtelesis.com

USA Headquarters | 19800 North Creek Parkway | Suite 200 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895
European Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11
Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830
www.alliedtelesis.com

© 2006 Allied Telesis Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-00579-05 Rev. G